

In the Claims:

1. (Previously Presented) A tweeter comprising:
a light, freely carried thin sandwich plate (3, 20, 39, 60) which can be excited into multiple reflected bending waves; and
at least one driver (1, 13, 14, 15, 26, 27, 28, 40, 41) which makes vibrating contact with and excites the sandwich plate (3, 20, 39, 60),
wherein the driver (1, 13, 14, 15, 26, 27, 28, 40, 41) is designed to excite at higher sound frequencies, the sandwich plate (3, 20, 39, 60) is designed for the propagation of bending waves with low damping, the sandwich plate (3, 20, 39, 60) is freely supported by holding elements (12, 24, 25, 34, 35) with low damping, and the holding elements (12, 24, 25, 34, 35) are designed to be low damping at higher sound frequencies,
wherein the bending waves have wavelengths smaller than a surface diagonal of the sandwich plate, and
wherein the sandwich plate has a bending resonance under a band containing the higher sound frequencies.
2. (Original) A tweeter as claimed in claim 1, wherein the sandwich plate (3) has two thin, hard cover plates (9, 10) with a shear resistant, thin core layer (11) placed between them.
3. (Original) A tweeter as claimed in claim 2, wherein the core layer (11) has a honeycomb structure.
4. (Original) A tweeter as claimed in claim 3, wherein the core layer (11) contains a spatially different distribution of the elasto-mechanical properties.
5. (Currently Amended) A tweeter as claimed in claim 4, wherein zonal thinning ~~and/or~~ or cutouts (53 to 55) are provided in the core layer ~~and/or~~ or the cover layers.
6. (Previously Presented) A tweeter as claimed in claim 5, wherein the size and arrangement of the zones (53 to 55) is such that a basic pattern is always repeated in a reduced scale.

7. (Currently Amended) ~~A tweeter comprising:~~

~~———— a light, freely carried thin sandwich plate (3, 20, 39, 60) which can be excited into multiple reflected bending waves,~~

~~———— at least one driver (1, 13, 14, 15, 26, 27, 28, 40, 41) which makes vibrating contact with and excites the sandwich plate (3, 20, 39, 60),~~

~~———— wherein the driver (1, 13, 14, 15, 26, 27, 28, 40, 41) is designed to excite at higher sound frequencies, the sandwich plate (3, 20, 39, 60) is designed for the propagation of bending waves with low damping, the sandwich plate (3, 20, 39, 60) is freely supported by holding elements (12, 24, 25, 34, 35) with low damping, and that the holding elements (12, 24, 25, 34, 35) are designed to be low damping at higher sound frequencies, The tweeter of claim 1,~~

wherein the sandwich plate (3) has two thin, hard cover plates (9, 10) with a shear resistant, thin core layer (11) placed between them,

wherein the core layer (11) contains a spatially different distribution of the elasto-mechanical properties,

wherein zonal thinning ~~and/or~~ or cutouts (53 to 55) are provided in the core layer ~~and/or~~ or the cover layers,

wherein the size and arrangement of the zones (53 to 55) is such that a basic pattern is always repeated in a reduced scale, and

wherein the core layer includes a foil which contains periodically repeated bulges (31) produced by embossing.

8. (Previously Presented) A tweeter as claimed in claim 7, wherein the bulges are shaped, arranged and directed is such that the maximum shear resistance is obtained in all moment directions.

9. (Currently Amended) A tweeter comprising:

a light, freely carried thin sandwich plate (3, 20, 39, 60) which can be excited into multiple reflected bending waves,

at least one driver (1, 13, 14, 15, 26, 27, 28, 40, 41) which makes vibrating contact with and excites the sandwich plate (3, 20, 39, 60),

wherein the driver (1, 13, 14, 15, 26, 27, 28, 40, 41) is designed to excite at higher sound frequencies, the sandwich plate (3, 20, 39, 60) is designed for the propagation of bending waves with low damping, the sandwich plate (3, 20, 39, 60) is freely supported by holding elements (12, 24, 25, 34, 35) with low damping, and that the holding elements (12, 24, 25, 34, 35) are designed to be low damping at higher sound frequencies,

wherein the sandwich plate (3) has two thin, hard cover plates (9, 10) with a shear resistant, thin core layer (11) placed between them,

wherein the core layer (11) contains a spatially different distribution of the elasto-mechanical properties,

wherein zonal thinning ~~and/or~~ or cutouts (53 to 55) are provided in the core layer ~~and/or~~ or the cover layers,

wherein the size and arrangement of the zones (53 to 55) is such that a basic pattern is always repeated in a reduced scale,

wherein the core layer includes a foil which contains periodically repeated bulges (31) produced by ~~embossing~~. embossing,

wherein the shape, arrangement and direction of the bulges is such that the maximum shear resistance is obtained in all moment directions, and

wherein the bulges are knobs (49, 50) in the form of a square based, four-sided pyramid, and the knobs (49, 50) are arranged to face in the same direction in strictly periodic, closely adjacent straight rows (47, 48), where each second row (48) alternately contains knobs in the opposite direction, and each row (47) is offset by half a knob (49, 50) with respect to the neighboring rows (48).

10. (Original) A tweeter as claimed in claim 9, wherein the holding elements (12, 24, 25, 34, 35) are suitable to be placed or inserted into a larger support structure (36).

11. (Original) A tweeter as claimed in claim 10, wherein one side of the holding elements is attached with a brittle-hard adhesive to the sandwich plate, and the other side is connected to the support structure.

12. (Original) A tweeter as claimed in claim 11, wherein the holding elements have edges, and that the edges are cemented in a brittle-hard manner to a cutout in the support structure.
13. (Original) A tweeter as claimed in claim 12, wherein the back side of the driver (40, 41, 46, 47) is designed as a holding element.
14. (Curently Amended) A tweeter as claimed in claim 13, wherein the plate diaphragm of a deep ~~and/or~~ or medium sound plate loudspeaker is designed as a support structure (36).
15. CANCEL.
16. (Currently Amended) A tweeter comprising:
a light, freely carried thin sandwich plate (3, 20, 39, 60) which can be excited into multiple reflected bending waves,
at least one driver (1, 13, 14, 15, 26, 27, 28, 40, 41) which makes vibrating contact with and excites the sandwich plate (3, 20, 39, 60),
wherein the driver (1, 13, 14, 15, 26, 27, 28, 40, 41) is designed to excite at higher sound frequencies, the sandwich plate (3, 20, 39, 60) is designed for the propagation of bending waves with low damping, the sandwich plate (3, 20, 39, 60) is freely supported by holding elements (12, 24, 25, 34, 35) with low damping, and that the holding elements (12, 24, 25, 34, 35) are designed to be low damping at higher sound frequencies,
wherein the sandwich plate (3) has two thin, hard cover plates (9, 10) with a shear resistant, thin core layer (11) placed between them,
wherein the core layer (11) contains a spatially different distribution of the elasto-mechanical properties,
wherein zonal thinning ~~and/or~~ or cutouts (53 to 55) are provided in the core layer ~~and/or~~ or the cover layers,
wherein the size and arrangement of the zones (53 to 55) is such that a basic pattern is always repeated in a reduced scale,

wherein the core layer includes a foil which contains periodically repeated bulges (31) produced by embossing, and

wherein the bulges are knobs (49, 50) in the form of a square based, four-sided pyramid, and the knobs (49, 50) are arranged to face in the same direction in strictly periodic, closely adjacent straight rows (47, 48), where each second row (48) alternatingly contains knobs in the opposite direction, and each row (47) is offset by half a knob (49, 50) with respect to the neighboring rows (48).

17. (Original) A tweeter as claimed in claim 1, wherein the holding elements (12, 24, 25, 34, 35) are suitable to be placed or inserted into a larger support structure (36).

18. (Original) A tweeter as claimed in claim 17, wherein one side of the holding elements is attached with a brittle-hard adhesive to the sandwich plate, and the other side is connected to the support structure.

19. (Original) A tweeter as claimed in claim 18, wherein the holding elements have edges, and that the edges are cemented in a brittle-hard manner to a cutout in the support structure.

20. (Original) A tweeter as claimed in claim 17, wherein the back side of the driver (40, 41, 46, 47) is designed as a holding element.

21. (Original) A tweeter as claimed in claim 17, wherein the plate diaphragm of a deep ~~and/or~~ or medium sound plate loudspeaker is designed as a support structure (36).

22. (Original) A tweeter as claimed in claim 2, wherein the core layer (11) contains a spatially different distribution of the elasto-mechanical properties.

23. (Previously Presented) A tweeter comprising:

a light, freely carried thin sandwich plate (3, 20, 39, 60) which can be excited into multiple reflected bending waves; and

at least one driver (1, 13, 14, 15, 26, 27, 28, 40, 41) which makes vibrating contact with and excites the sandwich plate (3, 20, 39, 60),

wherein the driver (1, 13, 14, 15, 26, 27, 28, 40, 41) is designed to excite at higher sound frequencies, the sandwich plate (3, 20, 39, 60) is designed for the propagation of bending waves with low damping, the sandwich plate (3, 20, 39, 60) is freely supported by holding elements (12, 24, 25, 34, 35) with low damping, and that the holding elements (12, 24, 25, 34, 35) are designed to be low damping at higher sound frequencies,

wherein the sandwich plate (3) has two thin, hard cover plates (9, 10) with a shear resistant, thin core layer (11) placed between them,

wherein the core layer includes a foil which contains periodically repeated bulges (31) produced by embossing, and

wherein the bulges are knobs (49, 50) in the form of a square based, four-sided pyramid, and the knobs (49, 50) are arranged to face in the same direction in strictly periodic, closely adjacent straight rows (47, 48), where each second row (48) alternately contains knobs in the opposite direction, and each row (47) is offset by half a knob (49, 50) with respect to the neighboring rows (48).

24. (Currently Amended) ~~A tweeter comprising:~~

~~— a light, freely carried thin sandwich plate (3, 20, 39, 60) which can be excited into multiple reflected bending waves; and~~

~~— at least one driver (1, 13, 14, 15, 26, 27, 28, 40, 41) which makes vibrating contact with and excites the sandwich plate (3, 20, 39, 60);~~

~~— wherein the driver (1, 13, 14, 15, 26, 27, 28, 40, 41) is designed to excite at higher sound frequencies, the sandwich plate (3, 20, 39, 60) is designed for the propagation of bending waves with low damping, the sandwich plate (3, 20, 39, 60) is freely supported by holding elements (12, 24, 25, 34, 35) with low damping, and that the holding elements (12, 24, 25, 34, 35) are designed to be low damping at higher sound frequencies.~~ The tweeter of claim 1 or claim 9 or claim 16, or claim 23,

wherein the sandwich plate (3) has two thin, hard cover plates (9, 10) with a shear resistant, thin core layer (11) placed between them, and

wherein the core layer includes a foil which contains periodically repeated bulges (31) produced by embossing.

25. (Currently Amended) The tweeter of claim 6, wherein the pattern has a fractal ~~arrangement~~ arrangement.